

Pump Performance Datasheet

Customer	:	Quote Number / ID	: 596697
Customer ref. / PO	:	Model	: NBS 012-070-2P
Tag Number	: 001	Stages	: 1
Service	:	Based on curve number	: 012-070-2P_Std
Quantity	: 1	Basic model number	: -
		Date last saved	: 04/21/2022 9:54 AM


Operating Conditions		Liquid	
Flow, rated	: 75.32 USgpm	Liquid type	: Cold Water
Differential head / pressure, rated (requested)	: 64.82 ft	Additional liquid description	:
Differential head / pressure, rated (actual)	: 64.82 ft	Solids diameter, max	: 0.00 in
Suction pressure, rated / max	: 0.00 / 0.00 psi.g	Solids concentration, by volume	: 0.00 %
NPSH available, rated	: Ample	Temperature, max	: 68.00 deg F
Site Supply Frequency	: 60 Hz	Fluid density, rated / max	: 1.000 / 1.000 SG

Performance		Material	
Speed, rated	: 3450 rpm	Material selected	: Cast iron / 125 Class

Impeller diameter, rated	: 4.29 in	Pressure Data	
Impeller diameter, maximum	: 6.97 in		
Impeller diameter, minimum	: 4.29 in	Maximum working pressure	: 35.11 psi.g
Efficiency	: 50.23 %	Maximum allowable working pressure	: 175.0 psi.g
NPSH required / margin required	: 4.74 / 0.00 ft	Maximum allowable suction pressure	: 130.0 psi.g
nq (imp. eye flow) / S (imp. eye flow)	: 18 / 115 Metric units	Hydrostatic test pressure	: 263.0 psi.g
MCSF	: 7.53 USgpm	Driver & Power Data (@Max density)	

Head, maximum, rated diameter	: 81.13 ft	Motor sizing specification	: Max power (non-overloading)
Head rise to shutoff	: 25.17 %	Margin over specification	: 0.00 %
Flow, best eff. point	: 75.32 USgpm	Service factor	: 1.15 (used)
Flow ratio, rated / BEP	: 100.00 %	Power, hydraulic	: 1.23 hp
Diameter ratio (rated / max)	: 61.55 %	Rated power (based on duty point)	: 2.45 hp
Head ratio (rated dia / max dia)	: 34.04 %	Max power (non-overloading)	: 2.80 hp
Cq/Ch/Ce/Cn [ANSI/HI 9.6.7-2010]	: 1.00 / 1.00 / 1.00 / 1.00	Nameplate motor rating	: 3.00 hp / 2.24 kW
Selection status	: Acceptable		

Energy Indexes	
PEI (CL)	: 0.92
ER (CL)	: 8



Construction Datasheet


Project name	Default	Tag Number	001
Consulting engineer		Service	
Customer		Model	NBS 012-070-2P
Customer ref. / PO		Quantity	1
Quote Number / ID	596697	Quoted By (Sales Office)	PFC EQUIPMENT INC
Date last saved	04/21/2022 9:54 AM	Quoted By (Sales Engineer)	Kelly Kresa

Construction Code : NBS 012-070/4.29AASG6S2ESBQQEIX2

Construction		Motor Information	
Product Family	NBS_Std	Manufacturer	Baldor
Suction Size	2 in.	Frame Size	182TC
Discharge Size	1.25 in.	Power	3 HP
Flange Rating	Class 125	RPM	3600
Orientation	Horizontal	Enclosure	TEFC
Rotation	Clockwise	Operating Power Supply	230/460/3/60
Pump Housing	Cast Iron, ASTM A48 - Class 35	Efficiency	Premium
O-Ring	EPDM	Service Factor	1.15
Plug	Galvanized	Motor Application	General Purpose
Impeller	Stainless Steel, AISI-304 / EN 1.430	Weight (Approx.)	
Impeller Nut	Stainless Steel, AISI-304	Pump	147.0 lb
Shaft	Stainless Steel, AISI 420	Support Rail	32.00 lb
Cover	Ductile Cast Iron, ASTM 70-50-05	Base Plate	-
Seal Type	Rubber bellows seal	Driver	66.00 lb
Shaft Seal	BQQE - Silicon carbide / Silicon carbide / EPDM	Estimated Shipping Gross Weight	245.0 lb
Seal Cap	Ductile Cast Iron, ASTM 70-50-05		
Motor Stool	Gray Cast Iron, ASTM Class 30		
Recirculation Line	None		
Coupling	Rigid, Axial Split Coupling (aluminum)		
Support Rail	Support Rail		

General Arrangement


Project name	: Default	Tag Number	: 001
Consulting engineer	:	Service	:
Customer	:	Model	: NBS 012-070-2P
Customer ref. / PO	:	Quantity of pumps	: 1
Quote Number / ID	: 596697	Quoted By (Sales Office)	: PFC EQUIPMENT INC
Date last saved	: 04/21/2022 9:54 AM	Quoted By (Sales Engineer)	: Kelly Kresa



NOT FOR CONSTRUCTION, UNLESS CERTIFIED AND REFERENCED ON ORDER


Units	Frame	DNS	DND	Class	A	AB	AG	B4	B7	D	D1	D2	E	G1	G2	H1	H2	H5	H6	H7	HG1	HG3	L	L4	L6	L7	L8	N2	Q	T	Weight
inches	182TC	2	1.25	125	3.13	5.88	15.63	10.45	11.42	4.50	0.69	0.69	3.75	4.53	5.08	5.25	7.00	1.75	2.50	7.00	0.20	0.20	14.64	13.75	12.25	7.75	3.13	7.48	9.54	8.69	245.0
Conditions of Service									Motor Data																						
Flow: 75.32 USgpm				Fluid: Cold Water				HP: 3				Encl: TEFC				Phase: 3					Efficiency: Premium										
TDH: 64.82 ft				Temp.: 68.00 deg F				RPM: 3450 rpm				Hz: 60				Voltage: 230/460					S.F.: 1.15										

Pump Performance Curve



Project name	: Default	Tag Number	: 001	Flow, rated	: 75.32 USgpm
Consulting engineer	:	Service	:	Differential head / pressure, rated	: 64.82 ft
Customer	:	Model	: NBS 012-070-2P	Rated power (based on duty point)	: 2.45 hp
Customer ref. / PO	:	Quantity	: 1	Max power (non-overloading)	: 2.80 hp
Quote Number / ID	: 596697	Quoted By (Sales Office)	: PFC EQUIPMENT INC	Efficiency	: 50.23 %
Date last saved	: 04/21/2022 9:54 AM	Quoted By (Sales Engineer)	: Kelly Kresa	Impeller diameter, rated	: 4.29 in
Based on curve number	: 012-070-2P_Std	Stages	: 1	PEI (CL)	: 0.92
		Speed, rated	: 3450 rpm	ER (CL)	: 8

Multi-Speed Performance Curve



Project name	: Default	Tag Number	: 001	Speed, rated	: 3450 rpm
Consulting engineer	:	Service	:	Flow, rated	: 75.32 USgpm
Customer	:	Model	: NBS 012-070-2P	Differential head / pressure, rated	: 64.82 ft
Customer ref. / PO	:	Quantity	: 1	Fluid density, rated / max	: 1.000 / 1.000 SG
Quote Number / ID	: 596697	Quoted By (Sales Office)	: PFC EQUIPMENT INC	Viscosity	: 1.00 cP
Date last saved	: 04/21/2022 9:54 AM	Quoted By (Sales Engineer)	: Kelly Kresa	Cq/Ch/Ce/Cn [ANSI/HI 9.6.7-2010]	: 1.00 / 1.00 / 1.00 / 1.00
		Stages	: 1	Based on curve number	: 012-070-2P_Std