

Pump Performance Datasheet

Customer	:		Quote Number / ID	:	596697
Customer ref. / PO	:		Model	:	NBS 015-070-2P
Tag Number	:	001	Stages	:	1
Service	:		Based on curve number	:	015-070-2P_Std
Quantity	:	1	Basic model number	:	-
			Date last saved	:	05/31/2022 10:25 AM

Operating Conditions		Liquid	
Flow, rated	: 227.3 USgpm	Liquid type	: Cold Water
Differential head / pressure, rated (requested)	: 107.7 ft	Additional liquid description	:
Differential head / pressure, rated (actual)	: 107.7 ft	Solids diameter, max	: 0.00 in
Suction pressure, rated / max	: 0.00 / 0.00 psi.g	Solids concentration, by volume	: 0.00 %
NPSH available, rated	: Ample	Temperature, max	: 68.00 deg F
Site Supply Frequency	: 60 Hz	Fluid density, rated / max	: 1.000 / 1.000 SG


Performance		Material	
Speed, rated	: 3450 rpm	Material selected	: Cast iron / 125 Class

Impeller diameter, rated	: 5.59 in		
Impeller diameter, maximum	: 6.93 in		
Impeller diameter, minimum	: 4.49 in		

Efficiency	: 76.01 %		
NPSH required / margin required	: 13.14 / 0.00 ft		
nq (imp. eye flow) / S (imp. eye flow)	: 24 / 143 Metric units		
MCSF	: 22.27 USgpm		
Head, maximum, rated diameter	: 131.4 ft		
Head rise to shutoff	: 22.02 %		
Flow, best eff. point	: 227.3 USgpm		
Flow ratio, rated / BEP	: 100.00 %		
Diameter ratio (rated / max)	: 80.66 %		
Head ratio (rated dia / max dia)	: 58.86 %		
Cq/Ch/Ce/Cn [ANSI/HI 9.6.7-2010]	: 1.00 / 1.00 / 1.00 / 1.00		
Selection status	: Acceptable		

Energy Indexes		Driver & Power Data (@Max density)	
----------------	--	------------------------------------	--

PEI (CL)	: 0.90	Motor sizing specification	: Max power (non-overloading)
ER (CL)	: 10	Margin over specification	: 0.00 %
		Service factor	: 1.15 (used)
		Power, hydraulic	: 6.18 hp
		Rated power (based on duty point)	: 8.13 hp
		Max power (non-overloading)	: 9.34 hp
		Nameplate motor rating	: 10.00 hp / 7.46 kW



Construction Datasheet

Project name	Default	Tag Number	001
Consulting engineer		Service	
Customer		Model	NBS 015-070-2P
Customer ref. / PO		Quantity	1
Quote Number / ID	596697	Quoted By (Sales Office)	PFC EQUIPMENT INC
Date last saved	05/31/2022 10:25 AM	Quoted By (Sales Engineer)	Kelly Kresa


Construction Code : NBS 015-070/5.59AASG6S2ESBQQEMX2

Construction		Motor Information	
Product Family	NBS_Std	Manufacturer	Baldor
Suction Size	2.5 in.	Frame Size	215TC
Discharge Size	1.5 in.	Power	10 HP
Flange Rating	Class 125	RPM	3600
Orientation	Horizontal	Enclosure	TEFC
Rotation	Clockwise	Operating Power Supply	230/460/3/60
Pump Housing	Cast Iron, ASTM A48 - Class 35	Efficiency	Premium
O-Ring	EPDM	Service Factor	1.15
Plug	Galvanized	Motor Application	General Purpose
Impeller	Stainless Steel, AISI-304 / EN 1.430	Weight (Approx.)	
Impeller Nut	Stainless Steel, AISI-304	Pump	166.0 lb
Shaft	Stainless Steel, AISI 420	Support Rail	24.00 lb
Cover	Ductile Cast Iron, ASTM 70-50-05	Base Plate	-
Seal Type	Rubber bellows seal	Driver	121.0 lb
Shaft Seal	BQQE - Silicon carbide / Silicon carbide / EPDM	Estimated Shipping Gross Weight	311.0 lb
Seal Cap	Ductile Cast Iron, ASTM 70-50-05		
Motor Stool	Gray Cast Iron, ASTM Class 30		
Recirculation Line	None		
Coupling	Rigid, Axial Split Coupling (aluminum)		
Support Rail	Support Rail		

General Arrangement

Project name : Default
 Consulting engineer :
 Customer :
 Customer ref. / PO :
 Quote Number / ID : 596697
 Date last saved : 05/31/2022 10:25 AM


Tag Number : 001
 Service :
 Model : NBS 015-070-2P
 Quantity of pumps : 1
 Quoted By (Sales Office) : PFC EQUIPMENT INC
 Quoted By (Sales Engineer) : Kelly Kresa



NOT FOR CONSTRUCTION, UNLESS CERTIFIED AND REFERENCED ON ORDER


Units	Frame	DNS	DND	Class	A	AB	AG	B4	B7	D	D1	D2	E	G1	G2	H1	H2	H5	H6	H7	HG1	HG3	L	L4	L6	L7	L8	N2	Q	T	Weight
inches	215TC	2.5	1.5	125	3.13	7.38	18.14	11.45	11.42	5.25	0.69	0.69	4.25	4.69	5.51	5.25	7.00	1.75	1.75	7.00	0.20	0.20	14.64	16.66	15.16	7.75	3.13	7.48	10.42	10.25	311.0
Conditions of Service										Motor Data																					
Flow: 227.3 USgpm				Fluid: Cold Water				HP: 10				Encl: TEFC				Phase: 3				Efficiency: Premium											
TDH: 107.7 ft				Temp.: 68.00 deg F				RPM: 3450 rpm				Hz: 60				Voltage: 230/460						S.F.: 1.15									

Pump Performance Curve



Project name	: Default	Tag Number	: 001	Flow, rated	: 227.3 USgpm
Consulting engineer	:	Service	:	Differential head / pressure, rated	: 107.7 ft
Customer	:	Model	: NBS 015-070-2P	Rated power (based on duty point)	: 8.13 hp
Customer ref. / PO	:	Quantity	: 1	Max power (non-overloading)	: 9.34 hp
Quote Number / ID	: 596697	Quoted By (Sales Office)	: PFC EQUIPMENT INC	Efficiency	: 76.01 %
Date last saved	: 05/31/2022 10:25 AM	Quoted By (Sales Engineer)	: Kelly Kresa	Impeller diameter, rated	: 5.59 in
Based on curve number	: 015-070-2P_Std	Stages	: 1	PEI (CL)	: 0.90
		Speed, rated	: 3450 rpm	ER (CL)	: 10

Multi-Speed Performance Curve



Project name	: Default	Tag Number	: 001	Speed, rated	: 3450 rpm
Consulting engineer	:	Service	:	Flow, rated	: 227.3 USgpm
Customer	:	Model	: NBS 015-070-2P	Differential head / pressure, rated	: 107.7 ft
Customer ref. / PO	:	Quantity	: 1	Fluid density, rated / max	: 1.000 / 1.000 SG
Quote Number / ID	: 596697	Quoted By (Sales Office)	: PFC EQUIPMENT INC	Viscosity	: 1.00 cP
Date last saved	: 05/31/2022 10:25 AM	Quoted By (Sales Engineer)	: Kelly Kresa	Cq/Ch/Ce/Cn [ANSI/HI 9.6.7-2010]	: 1.00 / 1.00 / 1.00 / 1.00
		Stages	: 1	Based on curve number	: 015-070-2P_Std