

PROJECT:	UNIT TAG:	QUANTITY:
REPRESENTATIVE:	TYPE OF SERVICE:	DATE:
ENGINEER:	SUBMITTED BY:	DATE:
CONTRACTOR:	APPROVED BY:	DATE:
	ORDER NO.:	





MTRE 1S-7/7 A-WB-A-HUUV

Vertical multistage centrifugal pump with integrated frequency converter designed for tank top mounting and for pumping of cooling lubricants and cutting oils for machine tools, cooling applications, industrial liquid transfer and similar applications.

Note! Product picture may differ from actual product

Conditions of Service	Pump Data	Motor Data
Liquid: Water	Max pressure at stated temp: 363 psi / 194 °F	Rated power - P2: 0.5 HP
Temperature: 68 °F	Liquid temperature range: 14 .. 194 °F	Rated voltage: 200-240 V
Specific Gravity: 1.000	Maximum ambient temperature: 122 °F	Mains frequency: 60 Hz
	Approvals motor: CE, RCM, cURus, IE5, IES2,	Enclosure class: IP55
	Shaft seal: HUUV	Insulation class: F
	Product number: 98400091	Motor protection: ELEC
		Motor type: 71A
		Eta 1/1: 84.0 %







Materials:
Impeller: Stainless steel
Impeller: AISI 304
Impeller: EN 1.4301
Material code: A





Qty.	Description
1	MTRE 1S-7/7 A-WB-A-HUUV  Product No.: 98400091 Multistage, immersible, self-priming, centrifugal pump for vertical installation in tanks etc. The pump head and base are in cast iron – all other wetted parts are in stainless steel. The pump has the following characteristics TEST: • Dimensions according to DIN 5440. • Impellers, intermediate chambers and spline shaft are made of Stainless steel. • Mechanical shaft seal according to EN 12756. • Power transmission via sintered metal split coupling. A cartridge shaft seal ensures high reliability, safe handling, and easy access and service. The pump is fitted with a 1-phase, fan-cooled, permanent-magnet, synchronous motor. The motor includes a frequency converter and PI controller in the motor terminal box. This enables continuously variable control of the motor speed, which again enables adaptation of the performance to a given requirement. The operating panel on the motor terminal box features a four-inch TFT display, push-buttons and the Grundfos Eye indicator. The display gives an intuitive and user-friendly interface to all functions. The push-buttons are used to navigate through the menu structure to access pump and performance data on site and enable setting of required setpoint as well as setting of pump to "Min." or "Max." operation or to "Stop". The Grundfos Eye indicator on the operating panel provides visual indication of pump status: • "Power on": Motor is running (rotating green indicator lights) or not running (permanently green indicator lights) • "Warning": Motor is still running (rotating yellow indicator lights) or has stopped (permanently yellow indicator lights) • "Alarm": Motor has stopped (flashing red indicator lights). Communication with the pump is also possible by means of Grundfos GO Remote (accessory). The remote control enables further settings as well as reading out of a number of parameters such as "Actual value", "Speed", "Power input" and total "Power consumption". The terminal box has a number of inputs and outputs enabling the motor to be used in advanced applications where many inputs and outputs are required: • two dedicated digital inputs • three analog inputs, 0(4)-20 mA, 0-5 V, 0-10 V, 0.5 - 3.5 V • 5 V voltage supply to potentiometer and sensor • one analog output, 0-10 V, 0(4)-20 mA • two configurable digital inputs or open-collector outputs • two Pt100/Pt1000 inputs • LiqTec, dry-running protection sensor input • Grundfos Digital Sensor input and output • 24 V voltage supply for sensors • two signal-relay outputs (potential-free contacts) • GENIbus connection • interface for Grundfos CIM fieldbus module. Controls: Frequency converter: Built-in Liquid: Pumped liquid: Water Liquid temperature range: 14 .. 194 °F Selected liquid temperature: 68 °F Density: 62.29 lb/ft³ Technical: Pump speed on which pump data are based: 3410 rpm Rated flow: 4.84 US GPM Rated head: 144.7 ft Chambers: 7

Qty.	Description
1	Drainage back to tank: N Pump orientation: Vertical Code for shaft seal: HUUV Approvals: CE Approvals on motor nameplate: CE, RCM, cURus, IE5, IES2, Curve tolerance: ISO9906:2012 3B Cable gland entry: 4xM20 blind plug Materials: Pump head: Cast iron EN 1561 EN-GJL-200 ASTM A48-25B Impeller: Stainless steel EN 1.4301 AISI 304 Installation: t max amb: 122 °F Maximum operating pressure: 362.59 psi Max pressure at stated temp: 363 psi / 194 °F Type of connection: NPT(F) Size of outlet connection: 1 1/4 inch Immersion depth: 9.84 in Flange size for motor: 56C Electrical data: Motor standard: NEMA Motor type: 71A IE Efficiency class: IE5 Rated power - P2: 0.5 HP Mains frequency: 60 Hz Suitable for 50/60 Hz: Y Rated voltage: 1 x 200-240 V Service factor: 1.0 Rated current: 2.40-2.10 A Cos phi - power factor: 0.96 Rated speed: 360-4000 rpm Efficiency: 84.0% Motor efficiency at full load: 84.0 % Enclosure class (IEC 34-5): IP55 Insulation class (IEC 85): F Motor No: 98362269 Cable gland entry: 4xM20 blind plug Others: Terminal box position: 6 Minimum efficiency index, MEI ≥: 0.67 Net weight: 38.2 lb Gross weight: 71.2 lb Shipping volume: 4.98 ft³ Country of origin: US Custom tariff no.: 8413.70.2040

98400091 MTRE 1S-7/7 A-WB-A-HUUV 60 Hz



Description	Value
General information:	
Product name:	MTRE 1S-7/7 A-WB-A-HUUV
Product No:	98400091
EAN number:	5711494356355
Technical:	
Pump speed on which pump data are based:	3410 rpm
Rated flow:	4.84 US GPM
Rated head:	144.7 ft
Chambers:	7
Impellers:	7
Number of reduced-diameter impellers:	0
Drainage back to tank:	N
Pump orientation:	Vertical
Code for shaft seal:	HUUV
Approvals:	CE
Approvals on motor nameplate:	CE, RCM, cURus, IE5, IES2,
Curve tolerance:	ISO9906:2012 3B
Pump version:	A
Model:	A
Cable gland entry:	4xM20 blind plug
Materials:	
Pump head:	Cast iron
Pump head:	EN 1561 EN-GJL-200
Pump head:	ASTM A48-25B
Impeller:	Stainless steel
Impeller:	EN 1.4301
Impeller:	AISI 304
Material code:	A
Installation:	
t max amb:	122 °F
Maximum operating pressure:	362.59 psi
Max pressure at stated temp:	363 psi / 194 °F
Type of connection:	NPT(F)
Size of outlet connection:	1 1/4 inch
Immersion depth:	9.84 in
Flange size for motor:	56C
Connect code:	WB
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	14 .. 194 °F
Selected liquid temperature:	68 °F
Density:	62.29 lb/ft³
Electrical data:	
Motor standard:	NEMA
Motor type:	71A
IE Efficiency class:	IE5
Rated power - P2:	0.5 HP
Mains frequency:	60 Hz
Suitable for 50/60 Hz:	Y
Rated voltage:	1 x 200-240 V
Service factor:	1.0
Rated current:	2.40-2.10 A
Cos phi - power factor:	0.96
Rated speed:	360-4000 rpm
Efficiency:	84.0%
Motor efficiency at full load:	84.0 %
Enclosure class (IEC 34-5):	IP55
Insulation class (IEC 85):	F
Built-in motor protection:	ELEC
Motor No:	98362269
Cable gland entry:	4xM20 blind plug
Controls:	
Control panel:	Graphical
Function Module:	FM300 - Advanced
Frequency converter:	Built-in






Company name:
Created by:
Phone:


Date: 13/01/2023

Description	Value
Others:	
Terminal box position:	6
Minimum efficiency index, MEI ≥:	0.67
Net weight:	38.2 lb
Gross weight:	71.2 lb
Shipping volume:	4.98 ft³
Country of origin:	US
Custom tariff no.:	8413.70.2040

98400091 MTRE 1S-7/7 A-WB-A-HUUV 60 Hz



98400091 MTRE 1S-7/7 A-WB-A-HUUV 60 Hz



98400091 MTRE 1S-7/7 A-WB-A-HUUV 60 Hz

