

PROJECT:	UNIT TAG:	QUANTITY:
REPRESENTATIVE:	TYPE OF SERVICE:	DATE:
ENGINEER:	SUBMITTED BY:	DATE:
CONTRACTOR:	APPROVED BY:	DATE:
	ORDER NO.:	DATE:





MTRE 45-2/1-1 A-G-A-HUUV

Vertical multistage centrifugal pump with integrated frequency converter designed for tank top mounting and for pumping of cooling lubricants and cutting oils for machine tools, cooling applications, industrial liquid transfer and similar applications.

Note! Product picture may differ from actual product


Conditions of Service	Pump Data	Motor Data
Efficiency: %	Max pressure at stated temp: 363 psi / 194 °F	Rated power - P2: 7.5 HP
Liquid: Emulsion	Liquid temperature range: 14 .. 194 °F	Rated voltage: 440-480 V
Temperature: 68 °F	Maximum ambient temperature: 122 °F	Mains frequency: 60 Hz
NPSH required: ft	Shaft seal: HUUV	Enclosure class: IP55
Specific Gravity: 1.000	Product number: 99077603	Insulation class: F
		Motor protection: ELEC
		Motor type: 132E
		Eta 1/1: 92.4 %





Materials:

Impeller: Stainless steel
Impeller: AISI 304
Impeller: EN 1.4301
Material code: A



Qty.	Description
1	MTRE 45-2/1-1 A-G-A-HUUV  Product No.: 99077603 Multistage, immersible, self-priming, centrifugal pump for vertical installation in tanks etc. The pump head and base are in cast iron – all other wetted parts are in stainless steel. The pump has the following characteristics TEST: • Dimensions according to DIN 5440. • Impellers, intermediate chambers and spline shaft are made of Stainless steel. • Mechanical shaft seal according to EN 12756. • Power transmission via sintered metal split coupling. A cartridge shaft seal ensures high reliability, safe handling, and easy access and service. The pump is fitted with a 3-phase, fan-cooled, permanent-magnet, synchronous motor. The motor includes a frequency converter and PI controller in the motor terminal box. This enables continuously variable control of the motor speed, which again enables adaptation of the performance to a given requirement. The operating panel on the motor terminal box features a four-inch TFT display, push-buttons and the Grundfos Eye indicator. The display gives an intuitive and user-friendly interface to all functions. The push-buttons are used to navigate through the menu structure to access pump and performance data on site and enable setting of required setpoint as well as setting of pump to "Min." or "Max." operation or to "Stop". The Grundfos Eye indicator on the operating panel provides visual indication of pump status: • "Power on": Motor is running (rotating green indicator lights) or not running (permanently green indicator lights) • "Warning": Motor is still running (rotating yellow indicator lights) or has stopped (permanently yellow indicator lights) • "Alarm": Motor has stopped (flashing red indicator lights). Communication with the pump is also possible by means of Grundfos GO Remote (accessory). The remote control enables further settings as well as reading out of a number of parameters such as "Actual value", "Speed", "Power input" and total "Power consumption". The terminal box has a number of inputs and outputs enabling the motor to be used in advanced applications where many inputs and outputs are required: • two dedicated digital inputs • three analog inputs, 0(4)-20 mA, 0-5 V, 0-10 V, 0.5 - 3.5 V • 5 V voltage supply to potentiometer and sensor • one analog output, 0-10 V, 0(4)-20 mA • two configurable digital inputs or open-collector outputs • two Pt100/Pt1000 inputs • LiqTec, dry-running protection sensor input • Grundfos Digital Sensor input and output • 24 V voltage supply for sensors • two signal-relay outputs (potential-free contacts) • GENIbus connection • interface for Grundfos CIM fieldbus module. Controls: Frequency converter: Built-in Liquid: Pumped liquid: Emulsion Liquid temperature range: 14 .. 194 °F Selected liquid temperature: 68 °F Density: 62.29 lb/ft³ Technical:




Company name: Specs
Created by:
Phone:


Date: 17/02/2023

Qty.	Description
1	Pump speed on which pump data are based: 3467 rpm Rated flow: 238 US GPM Rated head: 72.51 ft Chambers: 2 Drainage back to tank: N Pump orientation: Vertical Code for shaft seal: HUUUV Approvals: CE Approvals for motor: CE, RCM, cURus, IE5, IES2, UKCA, SEPRO Energy approvals for motor: CE Curve tolerance: ISO9906:2012 3B Cable gland entry: 5 x NPT 1/2" Materials: Pump head: Cast iron EN 1561 EN-GJL-200 ASTM A48-25B Impeller: Stainless steel EN 1.4301 AISI 304 Installation: t max amb: 122 °F Maximum operating pressure: 362.59 psi Max pressure at stated temp: 363 psi / 194 °F Type of connection: ANSI Size of outlet connection: 3 inch Immersion depth: 9.61 in Flange size for motor: 213TC Electrical data: Motor standard: NEMA Motor type: 132E IE Efficiency class: IE5 Rated power - P2: 7.5 HP Mains frequency: 60 Hz Suitable for 50/60 Hz: Y Rated voltage: 3 x 440-480 V Service factor: 1.15 Rated current: 9.10-8.50 A Cos phi - power factor: 0.91-0.89 Rated speed: 360-4000 rpm Motor efficiency at full load: 92.4 % Enclosure class (IEC 34-5): IP55 Insulation class (IEC 85): F Motor No: 99256773 Cable gland entry: 5 x NPT 1/2" Others: Terminal box position: 6 Minimum efficiency index, MEI ≥: 0.70 Net weight: 192 lb Gross weight: 256 lb Shipping volume: 16.9 ft³ Country of origin: US Custom tariff no.: 8413.70.2040


99077603 MTRE 45-2/1-1 A-G-A-HUUV 60 Hz






Pumped liquid = Emulsion
Liquid temperature during operation = 68 °F
Density = 62.29 lb/ft³



Description	Value
General information:	
Product name:	MTRE 45-2/1-1 A-G-A-HUUV
Product No:	99077603
EAN number:	5712606312153
Technical:	
Pump speed on which pump data are based:	3467 rpm
Rated flow:	238 US GPM
Rated head:	72.51 ft
Chambers:	2
Impellers:	1
Number of reduced-diameter impellers:	1
Drainage back to tank:	N
Pump orientation:	Vertical
Code for shaft seal:	HUUV
Approvals:	CE
Approvals for motor:	CE, RCM, cURus, IE5, IES2, UKCA, SEPRO
Energy approvals for motor:	CE
Curve tolerance:	ISO9906:2012 3B
Pump version:	A
Model:	B
Cable gland entry:	5 x NPT 1/2"
Materials:	
Pump head:	Cast iron
Pump head:	EN 1561 EN-GJL-200
Pump head:	ASTM A48-25B
Impeller:	Stainless steel
Impeller:	EN 1.4301
Impeller:	AISI 304
Material code:	A
Installation:	
t max amb:	122 °F
Maximum operating pressure:	362.59 psi
Max pressure at stated temp:	363 psi / 194 °F
Type of connection:	ANSI
Size of outlet connection:	3 inch
Immersion depth:	9.61 in
Flange size for motor:	213TC
Connect code:	G
Liquid:	
Pumped liquid:	Emulsion
Liquid temperature range:	14 .. 194 °F
Selected liquid temperature:	68 °F
Density:	62.29 lb/ft³
Electrical data:	
Motor standard:	NEMA
Motor type:	132E
IE Efficiency class:	IE5
Rated power - P2:	7.5 HP
Mains frequency:	60 Hz
Suitable for 50/60 Hz:	Y
Rated voltage:	3 x 440-480 V
Service factor:	1.15
Rated current:	9.10-8.50 A
Cos phi - power factor:	0.91-0.89
Rated speed:	360-4000 rpm
Motor efficiency at full load:	92.4 %
Enclosure class (IEC 34-5):	IP55
Insulation class (IEC 85):	F
Built-in motor protection:	ELEC



Pumped liquid = Emulsion
Liquid temperature during operation = 68 °F
Density = 62.29 lb/ft³






Company name: Specs
Created by:
Phone:


Date: 17/02/2023

Description	Value
Motor No:	99256773
Cable gland entry:	5 x NPT 1/2"
Controls:	
Control panel:	Graphical
Function Module:	FM300 - Advanced
Frequency converter:	Built-in
Others:	
Terminal box position:	6
Minimum efficiency index, MEI ≥:	0.70
Net weight:	192 lb
Gross weight:	256 lb
Shipping volume:	16.9 ft³
Country of origin:	US
Custom tariff no.:	8413.70.2040

99077603 MTRE 45-2/1-1 A-G-A-HUUV 60 Hz



99077603 MTRE 45-2/1-1 A-G-A-HUUV 60 Hz



99077603 MTRE 45-2/1-1 A-G-A-HUUV 60 Hz

